

hyperref package options

Sebastian Raatz, Heiko Oberdiek et al.

July 28th 2012

| | | |
|---------------------------------|---|--------------------------------------|
| <code>allbordercolors</code> | set all border color options | |
| <code>allcolors</code> | set all color options (without border and field options) | |
| <code>anchorcolor</code> | set color of anchors | <code>black</code> |
| <code>backref</code> | do bibliographical back references | <code>false</code> |
| <code>baseurl</code> | set base URL for document | <code>empty</code> |
| <code>bookmarks</code> | make bookmarks | <code>true</code> |
| <code>bookmarksnumbered</code> | put section numbers in bookmarks | <code>false</code> |
| <code>bookmarksopen</code> | open up bookmark tree | <code>false</code> |
| <code>bookmarksopenlevel</code> | level to which bookmarks are open | <code>\maxdimen</code> |
| <code>bookmarkstype</code> | to specify which ‘toc’ file to mimic | <code>toc</code> |
| <code>breaklinks</code> | allow links to break over lines | <code>false</code> |
| <code>citebordercolor</code> | color of border around cites | <code>0 1 0</code> |
| <code>citecolor</code> | color of citation links | <code>green</code> |
| <code>colorlinks</code> | color links | <code>false</code> |
| | | <code>true (tex4ht, dviwindo)</code> |
| <code>debug</code> | provide details of anchors defined | <code>false</code> |
| <code>destlabel</code> | destinations are named by the first <code>\label</code> after the anchor creation | <code>false</code> |
| | same as <code>verbose</code> | |
| <code>draft</code> | do not do any hyper linking | <code>false</code> |
| <code>driverfallback</code> | Use this driver option, if no driver is given and cannot be autodetected | |
| <code>dvipdfm</code> | use dvipdfm backend | |
| <code>dvipdfmx</code> | use dvipdfmx backend (dvipdfm) | |
| <code>dvips</code> | use dvips backend | |
| <code>dvipsone</code> | use dvipsone backend | |
| <code>dviwindo</code> | use dviwindo backend | |
| <code>encap</code> | to set encap character for hyperindex | |
| <code>extension</code> | suffix of linked files | <code>dvi</code> |
| <code>filebordercolor</code> | color of border around file links | <code>0 .5 .5</code> |
| <code>filecolor</code> | color of file links | <code>cyan</code> |
| <code>final</code> | opposite of option <code>draft</code> | <code>true</code> |
| <code>frenchlinks</code> | use small caps instead of color for links | <code>false</code> |
| <code>hidelinks</code> | hide links (no color, no border) | |
| <code>hyperfigures</code> | make figures hyper links | <code>false</code> |
| <code>hyperfootnotes</code> | set up hyperlinked footnotes | <code>true</code> |
| <code>hyperindex</code> | set up hyperlinked indices | <code>true</code> |
| <code>hypertex</code> | use HyperTeX backend | |
| <code>hypertextnames</code> | use guessable names for links | <code>true</code> |
| <code>implicit</code> | redefine L ^A T _E X internals | <code>true</code> |
| <code>latex2html</code> | use L ^A T _E X2HTML backend | |
| <code>linkbordercolor</code> | color of border around links | <code>1 0 0</code> |

| | | |
|--------------------------|--|-----------------------------|
| linkcolor | color of links | red |
| linktocpage | make page number, not text, be link on TOC, LOF and LOT | false |
| menubordercolor | color of border around menu links | 1 0 0 |
| menucolor | color for menu links | red |
| naturalnames | use L ^A T _E X-computed names for links | false |
| nesting | allow nesting of links | false |
| pageanchor | put an anchor on every page | true |
| pagebackref | backreference by page number | false |
| pdfauthor | text for PDF Author field | empty |
| pdfborder | width of PDF link border | 0 0 1 0 0 0 (colorlinks) |
| pdfcenterwindow | position the document window center of the screen | false |
| pdfcreator | text for PDF Creator field | LaTeX with hyperref package |
| pdfdirection | direction setting | empty |
| pdfdisplaydoctitle | display document title instead of file name in title bar | false |
| pdfduplex | paper handling option for print dialog | empty |
| pdf-fitwindow | resize document window to fit document size | false |
| pdfhighlight | set highlighting of PDF links | /I |
| pdfinfo | alternative interface for document information | empty |
| pdfkeywords | text for PDF Keywords field | empty |
| pdflang | PDF language identifier (RFC 3066) | empty |
| pdfmenubar | make PDF viewer's menu bar visible | true |
| pdfnewwindow | make links that open another PDF file start a new window | false |
| pdfnonfullscreenpagemode | page mode setting on exiting full-screen mode | empty |
| pdfnumcopies | number of printed copies | empty |
| pdfpagelayout | set layout of PDF pages | empty |
| pdfpagemode | set default mode of PDF display | empty |
| pdfpagelabels | set PDF page labels | false |
| pdfpagescrop | set crop size of PDF document | empty |
| pdfpagetransition | set PDF page transition style | empty |
| pdfpicktrackbypdfsize | set option for print dialog | empty |
| pdfprintarea | set /PrintArea of viewer preferences | empty |
| pdfprintclip | set /PrintClip of viewer preferences | empty |
| pdfprintpagerange | set /PrintPageRange of viewer preferences | empty |
| pdfprintscaling | page scaling option for print dialog | empty |
| pdfproducer | text for PDF Producer field | empty |
| pdfremotestartview | starting view for links into remote PDF documents | Fit |
| pdftrapped | set the document information Trapped entry | empty |
| pdfstartpage | page at which PDF document opens | 1 |
| pdfstartview | starting view of PDF document | Fit |
| pdfsubject | text for PDF Subject field | empty |
| pdf-tex | use pdfT _E X backend | |
| pdf-title | text for PDF Title field | empty |
| pdftoolbar | make PDF toolbar visible | true |

| | | |
|----------------|--|------------------|
| pdfview | PDF ‘view’ when on link traversal | <i>empty</i> |
| pdfviewarea | set /ViewArea of viewer preferences | <i>empty</i> |
| pdfviewclip | set /ViewClip of viewer preferences | <i>empty</i> |
| pdfwindowui | make PDF user interface elements visible | true |
| plainpages | do page number anchors as plain arabic | true |
| ps2pdf | use ps2pdf backend | |
| raiselinks | raise up links (for HyperTeX backend) | false |
| runbordercolor | color of border around ‘run’ links | 0 .7 .7 |
| runcolor | color of ‘run’ links | filecolor |
| setpagesize | set page size by special driver commands | true |
| tex4ht | use T _E X4ht backend | |
| textures | use Textures backend | |
| unicode | Unicode encoded pdf strings | |
| urlbordercolor | color of border around URL links | 0 1 1 |
| urlcolor | color of URL links | magenta |
| verbose | be chatty | false |
| vtex | use V _T E _X backend | |
| vtexpdfmark | use backend for V _T E _X in PDF/PS mode (pdfmark specials) | |
| xetex | use XeTeX backend (dvipdfm) | |
